# **ChemGrout**°



# CG-600 **Compact Colloidal Series**

The CG600/8CF combines the latest advances in colloidal grouting in a compact design. These field proven grout plants feature ChemGrout's 8 cubic foot capacity "Turbomixer", along with a rotating bridge breaker, nine cubic foot capacity vertical shaft paddle agitator, and a 3-stage size 6 closed throat progressive cavity pump. Mixer and pump are mounted on a single skid (transportable by pick-up truck) for quick, easy set-up and immediate operation.

## **Specifications**

| PUMP                | 270                                 |
|---------------------|-------------------------------------|
| Pump Type           | 3L6 progressing cavity              |
| Output/Pressure     | 20 gpm, 261 psi                     |
| COLLOIDAL MIXER     |                                     |
| Mix Tank            | 8 c.f. with bottom cleanout         |
| Mixing Pump         | 2 x 3 x 6 diffuser-type centrifugal |
| Holding Tank        | 9 c.f. or 13 c.f. paddle agitating  |
|                     |                                     |
| PHYSICAL SPECIFICAT | IONS                                |
|                     |                                     |
| Weight              | ~1200 lbs                           |
| Size                | 88"L x 34"W x 59"H                  |
| Power Required      | 250 cfm, 100 psi (air)              |
| Hydraulic           |                                     |
| Weight              | ~1200 lbs                           |
| Size                | 88"L x 34"W x 59"H                  |
| Power Required      | Dual Circuits, 12/12 gpm, 2000 psi  |
| POWER PACKS         |                                     |
| Electric/Hydraulic  |                                     |
| Weight              | Varies                              |
| Size                | Varies by Voltage                   |
| Power Required      | 25 HP, several voltages available   |
| Diesel/Hydraulic    |                                     |
| Weight              | ~1750 lbs.                          |

weigh Size 74"L x 34"W x 37"H **Power Required** 27 HP Diesel/electric start



# CG-625 **Colloidal Grout Plant** 20 gpm; trailer mount

Mounted on a heavy-duty, highway ready trailer, this unit was originally designed for highway pavement undersealing. It is also useful for slabjacking or other grouting projects requiring cementitious slurries. It features an 8 cubic foot colloidal mixer and an 9 or 13 cubic foot holding hopper with a two stage, open throat pump. The trailer is highway ready. Available in diesel power only.

### **Specifications**

#### PUMP

| Pump Type      | 2C6 progressing cavity                        |  |
|----------------|---|--|
| Output/Pressur | re Variable up to 20 gpm, 174 psi             |  |
| COLLOIDAL MIXI | ER CONCUSSION CONCUSSION                      |  |
| Mix Tank       | 8 c.f. with bottom cleanout                   |  |
| Mixing Pump    | 2 x 3 x 6 diffuser-type centrifugal           |  |
| Holding Tank   | 9 or 13 c.f. paddle agitating                 |  |
| DRIVE POWER    |   |  |
| Model          | Three cylinder air cooled 37 HP diesel engine |  |

#### Model

| PHYSICAL SPECIFICATIONS  |                     |
|--------------------------|---------------------|
| Trailer Mount Dimensions | 132"L x 72"W x 72"H |
| Trailer Mount Weight     | ~4200 pounds        |