

"Equipment for Grouting Since 1969"

805 E. 31st Street, P.O. Box 1140

LaGrange Park, Illinois 60526

Phone: 708-354-7112 **Fax**: 708-354-3881

Manufacturer: MAPEI Contact: Kelly Page

1851 NW 22nd Street **Phone:** 954-485-8575 Fort Lauderdale, FL 33311 **Fax:** 954-485-2032

Material Testing Results

info@chemgrout.com

www.chemgrout.com

Date: 7/13/00

E-Mail:

Web Site:

Material: Nova/Plan 2 Lot # L271906

Material Application: Self-leveling, Normal set, Polymer modified, Floor underlayment.

Mfg. Plant: N/A Std. Bag Weight 55#

Environmental Conditions: Outside Temperature 81.1*F Humidity 55%

Equipment Used: Model CG570 Pump 2TJ6

Mixer Paddle Power Hydraulic

Mixing Water Temp: 80.6 *F

Batching Method: Quantity Material 165 lbs. Quantity Water 41 lbs

Mixing Time: 30-40 Seconds

Batch Temp: 87.7 *F

Specific Gravity: Material Weight 272 grams SG = 1.94

Water Weight 140 grams

Flow Cone 28 Seconds

Sieve Analysis: Weight Retained No. 4 No. 50

(grams) No. 8 No. 100

No. 16 No. 200 No. 30 Pan

Pumping Method: Hose Dia. & Lengths used (one) 50' L x 1 1/4" I.D.

Recirculated through hose, recorded pressures at various flow rates

Observations: Polymer bleed noticed on top of pump hopper

Mixer easy, smooth creamy looking product

Results: ChemGrout rates the pumpability of this product as "excellent" with a rating of

"A". All ChemGrout models can mix and pump this material.