

*"Equipment for Grouting Since 1969"* 805 E. 31st Street, P.O. Box 1140 LaGrange Park, Illinois 60526 **Phone**: 708-354-7112 **Fax**: 708-354-3881

## **Material Testing Results**

Date: 10/31/00 E-Mail: info@chemgrout.com Web Site: www.chemgrout.com

	22nd Street erdale, FL 33311	Contact:Kelly PagePhone:954-485-8575Fax:954-485-2032
Material: Novotop "	Gris Grey"	Lot # A31E072
Material Application: Self-leveling, Abrasion resistant, Concrete topping		
Mfg. Plant: Not Available		Std. Bag Weight 50#
Environmental Conditions	s: Outside Temperature 82.5*F	Humidity 56%
Equipment Used:	Model CG570 Mixer Paddle	Pump2TJ6 Progressing CavityPowerHydraulic
Mixing Water Temp:	75 *F	
Batching Method:	Quantity Material 150 lbs.	Quantity Water 31.3 lbs
Mixing Time:	50-60 Seconds	
Batch Temp:	95.7 *F	
Specific Gravity:	Material Weight257 gramsWater Weight140 grams	SG = 1.84
Flow Cone	19 Seconds	
Sieve Analysis:	Weight Retained No. 4 (grams) No. 8 No. 16 No. 30	No. 50 No. 100 No. 200 Pan
Pumping Method:	Hose Dia. & Lengths used (one) 50' L x 1 1/4" I.D. Recirculated through hose, recorded pressures at various flow rates	
Observations:	Larger partical size than other MAPEI underlayments Very easy to pump Lumps hard to break up in mixer	
Results:	ChemGrout rates the pumpability of "A". All ChemGrout models of	y of this product as "Excellent" with a rating can mix and pump this material. Mapei Novaton Gris (