

Material Testing Results

"Equipment for Grouting Since 1969"
805 E. 31st Street, P.O. Box 1140

Date: 10/31/00

Manufacturer: MAPEI Contact: Kelly Page

 1851 NW 22nd Street
 Phone:
 954-485-8575

 Fort Lauderdale, FL 33311
 Fax:
 954-485-2032

Material: Planiseal 88 Lot # AZ9C980

Material Application: One component, Polymer modified, Coating / Mortar for protection of concrete

and masonry

Mfg. Plant: Not Available Std. Bag Weight 55#

Environmental Conditions: Outside Temperature 84*F Humidity 50%

Equipment Used: Model CG570 Pump 2TJ6 Progressing Cavity

Mixer Paddle Power Hydraulic

Mixing Water Temp: 73.4 *F

Batching Method: Quantity Material 165 lbs. Quantity Water 41.3 lbs

Mixing Time: 50-60 Seconds

Batch Temp: 88.4 *F

Specific Gravity: Material Weight 212 grams SG = 1.51

Water Weight 140 grams

Flow Cone N/A - too thick, would not flow Seconds

Sieve Analysis: Weight Retained No. 4 No. 50

(grams) No. 8 No. 100

No. 16 No. 200 No. 30 Pan

Pumping Method: Hose Dia. & Lengths used (one) 50' L x 1 1/4" I.D

Recirculated through hose, recorded pressures at various flow rates.

Observations: Smooth creamy looking product, too thick to flow through flow cone,

Pumped very easy considering how thick the product was, okay for spray

applications, suprising low discharge pressures

Results: ChemGrout rates the pumpability of this product as "Excellent" with a rating

of "A". All ChemGrout models can mix and pump this material.