

"Equipment for Grouting Since 1969"

Material Testing Results

"Equipment for Grouting Since 1969" 805 E. 31st Street, P.O. Box 1140 LaGrange Park, Illinois 60526			E-Mail: in		August 8, 2000 info@chemgrout.com	
Phone : 708-354-7112	Fax : 708-354-3881		Web Site: v		www.chemgrout.com	
Manufacturer:	Vesuvius - Buffalo 661 Willet Road Buffalo, NY 14218		Contact: Phone: Fax:	608	nnis Heuer 3-288-8221 3-288-8225	
Material:	Basilite 75		Lot #	N/A	Α	
Material Application:	Ladle maintenance lining for "Gray Iron & Steel"					
Mfg. Plant:	Maple Grove, OH		Std. Bag Weight: 50 #			
Testing Conditions:	Outside Temperatu	ıre: 82.5*F	Humidity:		61%	
Equipment Used:	Model: CG570 Mixer: Paddle		Pump: 2TJ6 Pr Power: Hydrau		rogressing Cavity Ilic	
Std. Mix Ratios:	18 lbs. water per bag		Water Temp:		77.8 *F	
Batching Method:	Quantity Material:	198 lbs.	Quantity V	Water:	54 lbs	
Mixing Time:	70-80 Seconds		Batch Temp:		86.7 *F	
Specific Gravity:	SG = 1.96		Flow Cone		N/A Seconds	
Pumping Method:	Recirculated throu	gh hose, recorded	l pressures a	t variou	s flow rates.	
Flow Rate/Pressure:	Flow Rate	Pressure	Flow Rate		Pressure	
Hose (12.5' Long x 1 1/4" I.D.)		13 PSI	GPM		PSI	
Hose ()	8.4 GPM	18 PSI	GPM		PSI	
Hose ()	9.4 GPM	21 PSI	GPM		PSI	
Hose ()	10.7 GPM	26 PSI GPM		Л	PSI	
Hose ()	16.1 GPM			Λ	PSI	
Hose ()	18.8 GPM 55 PSI		GPM		PSI	
Hose ()	21.0 GPM	65 PSI	GPN GPN		PSI	
Hose ()	GPM				PSI	
Hose () Hose ()	GPM GPM	PSI PSI	GPN GPN		PSI PSI	
Observations:	Batch was too thin at Std. mix ratio, added 48 lbs. more material, sprayed good mixed easy, very sandy product					
Results:	ChemGrout, Inc. rates the pumpability of this product as a 7 on a scale of 10, w 10 being the easiest. ChemGrout, Inc. recommends a CG050 pump or higher.					