



CG-050 Grout Pump



Product Page:

<https://www.chemgrout.com/products/grout-pumps/piston-grout-pumps-grout-pumps/cg-050-grout-pump/>

Product Summary

Product Description

The ChemGrout model CG-050 is a portable, skid mounted, air or hydraulic powered grout pump. The lightweight aluminum construction makes this model portable for hard to reach jobs. The holding hopper is connected directly to the suction of the grout pump to provide a continuous pumping operation. The grout pump is a 2" positive displacement, pulsating piston. This grout pump is available with either an air or hydraulic cylinder to power the pump. All components are easily accessible for operating, cleaning and maintenance. The pump comes complete and ready to use with a 12.5 foot grout hose and a set of spare piston cups.

Applications

marine/underwater, hollow metal filling, door frames, window frames, precast, machine base, undersealing, slab raising, and encasements.

Specifications

Model # Piston Pump Model Power Hopper Max. Output Max. Pressure

CG050

2" Piston Pump

Air

5 gallon

5 GPM

225 PSI (16 Bar)

CG050/H

2" Piston Pump High Pressure

Hyd.

5 gallon

5 GPM

400 PSI (28 Bar)

Requirements, Weights, and Dimensions

Model Number Description / Requirements Dimensions Weight

CG050

Skid Mounted Air Pwd

Requires 15 CFM, 100 PSI

44" L X 11" W X 24" H

55 lbs.

CG050/H

Skid Mounted Hyd. Pwd

Requires 5 GPM, 1000 PSI

44" L X 11" W X 24" H

95 lbs.

Product Gallery

