



CG-QUATTRO Continuous Mix Grout Plant



Product Page:

<https://www.chemgrout.com/products/specialty-equipment/cg-quattro-continuous-mix-grout-plant/>

Product Summary

Product Description

The ChemGrout model CGQUATTRO is a wheel mounted, electric powered, continuous mixing grout machine that is designed to continuous mixing and pump cementitious grout materials like self-leveling underlayments. An optional air compressor allows spray applications for plasters, EFIS, stuccos and fireproofing materials. This compact design allows easy movement through doorways for access

to the job site. The Quattro includes a large hopper for dry material, a rotor/stator pump, water pump and remote control. The hopper holds up to 8 bags of dry material. The rotor/stator pump deliver up to 13 GPM, 580 PSI. The water pump delivers constant pressure to the mixing chamber for consistent quality. The remote control is used to shut the Quattro off from the end of the hose. The rugged steel frame stands up to the toughest conditions on the job site. Operator controls are centrally located for efficient production. The pumping components disassemble quickly for fast and efficient cleaning. An optional air compressor supplies the air for the spray wand and can be used as a remote control to shut the Quattro off from the end of the hose. All components are easily accessible for operating, cleaning and maintenance. This system requires 440V, 20 A, 3 phase electric power. Pricing includes 100 foot of material discharge hose, cleaning kit, tool kit, and spare rotor/stator. The optional air compressor includes 100 feet of air hose and the spray wand

Applications

Self leveling floor underlayments, plastering, stucco, EFIS, fireproofing, resurfacing deteriorated concrete, waterproofing, mortar spraying, seal coating concrete and finishing concrete.

Specifications

Model Progressive Cavity Pump Model Bag Hopper Max. Output Max. Pressure

CGQUATTRO

Several Rotor/Stator combinations depending on type material used

4.5 Cubic Foot

5-13 GPM

580 PSI

Requirements, Weights, and Dimensions

Model Number Description Dimensions Weight

CGQUATTRO

Wheel Mounted, Electric Powered, Continuous Mix, Grout Plant

Requires 440 V, 20 Amp, 3 Phase Electricity

44 L X 26 W X 58 H

408 lbs