

ChemGrout®

CG-550 Rugged High-Pressure Series

Combines ease of operation and low maintenance to provide the ultimate in performance.

**CG550/030/GHES/HP
Gas/Hydraulic**

**CG550/030/A/HP
Air Powered**



Single operator system – 45 gallon (170 liter) mixing tank, large holding hopper and centrally located controls allow a single operator to mix, transfer and pump for continuous production.

**CG555/030/DHES/HP
Diesel/Hydraulic**



Efficiently mixes and pumps most pre-packed non-shrink grouts and repair mortars. Materials include bentonites, cement/sand and most slurry products.

Outputs to 16 gpm (60 lpm), 700 psi (48 bar).


Power options include air, electric/hydraulic, hydraulic, gas/hydraulic and diesel/hydraulic.

Pump completely disassembles with only a hammer for fast and thorough cleaning.

ChemGrout®

Widest Selection of Grouting Equipment in the World

**CG-030HP
Rapid U-clip
Disassembly**



The Rugged HP Series features a single acting, variable speed 3" piston pump that provides the versatility to handle materials ranging from fluid slurries to heavily sanded grouts. Materials commonly used with the CG-030 include cement slurries, sanded cement mixes, bentonite mixes (with or without sand), most repair mortars, high-strength non-shrink grouts and self-leveling products.


The CG-030 is engineered for ease of operation and low cost maintenance. The unique staple lock construction holds all working components together allowing parts to be easily accessed for cleaning and maintenance.

The large capacity hopper is mounted above the suction housing, enabling a new batch to be mixed while the first is being pumped. This helps to provide a consistent "non-stop" discharge of material, virtually eliminating the clogging of hose lines.

Specifications

CG030 Skid - Power	Max. Output/Pressure	Required	Weight	Size
Air	16 gpm (60 lpm), 700 psi (48 bar)	100 cfm, 100 psi	310 lbs	64" x 31" x 29"
Hydraulic	12 gpm (45 lpm), 700 psi (48 bar)	9 gpm, 1800 psi	290 lbs	64" x 31" x 29"
CG550/030 Skid Power	Max. Output/Pressure	Required	Weight	Size
Air	16 gpm (60 lpm), 700 psi (48 bar)	185 cfm, 100 psi	490 lbs	64" x 31" x 56"
Hydraulic	12 gpm (45 lpm), 700 psi (48 bar)	2 Supplies each - 10 & 6 gpm, 1800 psi	450 lbs	64" x 31" x 56"
Electric/Hydraulic	12 gpm (45 lpm), 700 psi (48 bar)	*3 Phase	955 lbs	78" x 31" x 56"
Gas/Hydraulic, Electric Start	12 gpm (45 lpm), 700 psi (48 bar)	Skid Mounted Gas/Hydraulic Grout Plant Self-Contained, 20 HP Honda Gas Engine	955 lbs	78" x 31" x 56"
Diesel/Hydraulic, Electric Start	12 gpm (45 lpm), 700 psi (48 bar)	Skid Mounted Diesel/Hydraulic Grout Plant Self-Contained, 20 HP Kubota Diesel Engine	1050 lbs	78" x 31" x 56"
CG555/030 Trailer - Pwr	Max. Output/Pressure	Required	Weight	Size
Gas/Hydraulic	12 gpm (45 lpm), 700 psi (48 bar)	Skid Mounted Gas/Hydraulic Grout Plant Self-Contained, 20 HP Honda Gas Engine	1400 lbs	110" x 68" x 70"
Diesel/Hydraulic	12 gpm (45 lpm), 700 psi (48 bar)	Skid Mounted Diesel/Hydraulic Grout Plant Self-Contained, 20 HP Kubota Diesel Engine	1495 lbs	110" x 68" x 70"

**CG030HP
Piston
Pump Skid
Mounted**



Complete grouting systems combine the CG-030 piston pump with a high efficiency paddle mixer to provide a continuous output of material. Both mixer and pump are equipped with their own variable speed control.

The large 45-gallon mix tank* features specially designed blades and baffles that develop a high shearing action, insuring rapid and thorough mixing. After mixing, the material is transferred to a holding hopper through a slide gate designed to handle the most difficult materials. Holding hoppers are available in 15-gallon (57 liter) or 30-gallon (113 liter) sizes and are matched based on material flow.

The compact skid mounted CG550/030/HP is offered in a variety of power options, and is also available in a gas/hydraulic or diesel/hydraulic trailer version. The trailer mounted CG-555 is a fully integrated system combining mixer, pump and power system, all in a single road worthy package.

* A second mix tank can be added at additional cost.


Accessories

Grout Hose. Equipped with quick disconnect fittings. Available in 25 and 50 foot lengths.




Water Meters. Available in manual or automatic. Accurately measures the water for each batch.

In-Line High-Pressure Gauge.



Working pressures up to 1000 psi.



Mechanical Surface Packer.

Equipped with shut-off valve and a quick disconnect fitting.

*Several Voltages Available

Applications include:

Soil rails, tiebacks, earth anchors, cable & rock bolts, foundation stabilization, soil compaction, pavement undersealing, slabjacking, slab raising, underwater foundations, piers, deep well casing, well sealing, machine bases, abandonment, geothermal and environmental remediation.



Widest Selection of Grouting Equipment in the World